%PDF-1.4 1 0 obj << /Title (bÿ) /Creator (bÿ) /Producer (bÿQt 4.8.4 \(C\) 2011 Nokia Corporation and/or its subsidiary\(-ies\)) /CreationDate (D:20181005184509-07'00') >> endobj 3 0 obj << /Type /ExtGState /SA true /SM 0.02 /ca 1.0 /CA 1.0 /AIS false /SMask /None>> endobj 4 0 obj [/Pattern /DeviceRGB] endobj 6 0 obj << /Type /XObject /Subtype /Image /Width 250 /Height 250 /BitsPerComponent 8 /ColorSpace /DeviceGray /Length 7 0 R /Filter /FlateDecode >> stream

This page contains binary/encoded PDF stream data that is not human-readable text. The visible content consists of corrupted character data and embedded PDF object definitions including font descriptors and stream objects.

Partial readable PDF structure:

```
endstream endobj 15 0 obj 9555 endobj 18 0 obj << /Type /FontDescriptor /FontName /QSAAAA+Arial-ItalicMT /Flags 4 /FontBBox [-517.089843 -324.707031 1081.54296 997.558593 ] /ItalicAngle 0 /Ascent 905.273437 /Descent -211.914062 /CapHeight 905.273437 /StemV 73.2421875 /FontFile2 19 0 R >> endobj 19 0 obj << /Length1 4836 /Length 22 0 R /Filter /FlateDecode >> stream
```

```
endstream endobj 22 0 obj 2599 endobj 20 0 obj << /Type /Font /Subtype /CIDFontType2 /BaseFont /Arial-ItalicMT /CIDSystemInfo << /Registry (Adobe) /Ordering (Identity) /Supplement 0 >> /FontDescriptor 18 0 R /CIDToGIDMap /Identity /W [0 [744 552 552 552 496 220 276 552 552 ] ] >> endobj 21 0 obj << /Length 420 >> stream /CIDInit /ProcSet findresource begin 12 dict begin begincmap /CIDSystemInfo << /Registry (Adobe) /Ordering (UCS) /Supplement 0 >> def /CMapName /Adobe-Identity-UCS def /CMapType 2 def 1 begincodespacerange <0000> endcodespacerange 2 beginbfrange <0000> <0000> <0000> <0001> <0008> [<0075> <006E> <0061> <0073> <0069> <0074> <0065> <0064> ] endbfrange endcmap CMapName currentdict /CMap defineresource pop end end endstream endobj 12 0 obj << /Type /Font /Subtype /Type0 /BaseFont /Arial-ItalicMT /Encoding /Identity-H /DescendantFonts [20 0 R] /ToUnicode 21 0 R>> endobj 23 0 obj << /Type /FontDescriptor /FontName /QXAAAA+ArialMT /Flags 4 /FontBBox [-664.550781 -324.707031 2000 1005.85937 ] /ItalicAngle 0 /Ascent 905.273437 /Descent -211.914062 /CapHeight 905.273437 /StemV 73.2421875 /FontFile2 24 0 R >> endobj 24 0 obj << /Length1 9500 /Length 27 0 R /Filter /FlateDecode >> stream
```

endstream endobj 27 0 obj 6475 endobj 25 0 obj << /Type /Font /Subtype /CIDFontType2 /BaseFont /ArialMT /CIDSystemInfo << /Registry (Adobe) /Ordering (Identity) /Supplement 0 >> /FontDescriptor 23 0 R /CIDToGIDMap /Identity /W [0 [744 552 662 552 496 276 552 552 276 552 226 936 552 496 552 552 552 772 330 496 516 552 552 552 552 662 220 496 552 716 552 662 220 496 552 716 552 552 662 496 606 552 826 662 662 496 330 552 662 552 662 716 552 496 606 716 276 276 276 276 330 330 276 772 276 496]] >> endobj 26 0 obj << /Length 805 >> stream /CIDInit /ProcSet findresource begin 12 dict begin begincmap /CIDSystemInfo << /Registry (Adobe) /Ordering (UCS) /Supplement 0 >> def /CMapName /Adobe-Identity-UCS def /CMapType 2 def 1 begincodespacerange <0000> endcodespacerange 2 beginbfrange <0000> <0000> <0000> <0001> <003F> [<0035> <0050> <0061> <0079> <0074> <006F> <006E> <0009> <0057> <0065> <0073> <006C> <0030> <0037> <0036> <0047> <0072> <0063> <0044> <0075> <0067> <0039> <0031> <0056> <0069> <006B> <0033> <004E> <0038> <0034> <004D> <0043> <0052> <0068> <0064> <0041> <0078> <0054> <0032> <006D> <0042> <0053> <004A> <002D> <0062> <004B> <004C> <0045> <0077> <0070> <0076> <0046> <0048> <003A> <0049> <0066> <002C> <0028> <0029> <002E> <004F> <003B> <007A>] endbfrange endcmap CMapName currentdict /CMap defineresource pop end end endstream endobj 11 0 obj << /Type /Font /Subtype /Type0 /BaseFont /ArialMT /Encoding /Identity-H /DescendantFonts [25 0 R] /ToUnicode 26 0 R>> endobj 28 0 obj << /Type /FontDescriptor /FontName /QCBAAA+Arial-BoldMT /Flags 4 /FontBBox [-627.929687 -376.464843 2000 1010.25390] /ItalicAngle 0 /Ascent 905.273437 /Descent -211.914062 /CapHeight 905.273437 /StemV 104.980468 /FontFile2 29 0 R >> endobj 29 0 obj << /Length1 9388 /Length 32 0 R /Filter /FlateDecode >> stream

×>"‰g:¿ ʽBÍ¿¡œ¢ìS Q~©*Vµ©Ž©N©½Ôõêmê—Õ_i"4¹šVÍ#šßk.{„yĬõ°y<iñ¾ÇWSø)%S d e'"Z=É ý5*¾$D _Æî 6s kQš# (–i ™ Q2Í È i%™ kdZ…
ô>™V"Sã|4Xß 'i ² ŽÉ´ w"Ë ×Îl_–i Je€Ls„Wn i bì ižLQ®–i%ñT 'i ÒGeZM óÑ éÊ$™ö
eÊ 2í ÍÊ›È x ÊòV/"ižÌP×1Z‰ýSÔ+dš' êeŒEVa¿J½C¦yâ«^Ïh5ÅM}D¦ +õ Fk° ßS}\¦y2]ý(£=dü%ZÂ_¢%ü%ZÂ_¢%ü%ZÂ_¢%ü%ZÂ_¢%ü%ZÂ_¢%ü)=…
Ùþ†LSÛ_bôTZÏ©?•iž„«/0Ú"ê¦ádšÚø £½±ßG#È4OB5þŒö¦|äù>Œ 4ß b¨É"ïÄPcd´?ÕGS#Ó¨ FÂ!ûý5Ý2Í A#ù+ ÍߢÓt¾„l0›ÿ LÓù B}ª9+ÓèSÍ
F‡1Ÿ 'iêSÉw lþ ™¦óßdt õ©æºL£O5W OññPÉ4â£¹Áè$ÊÇc†L# oJk&à¯™€¿f,]š
vyN¯ï9a¾ç ¿xŽùà1" 4Œ#É@ª‰t +>«‰ ôáå$ƒ¤Ÿõ"Ë 4½[° ßÆf$ãH éÁ¿@ °o)¾ï$ ¬eÅ§ g¯À{'Î,BÚ†ïÒ¹66Ç,—"ñëÄ9½øt åØg']ÿ](×>ÆQz¯ [6lQé æW'›k•%÷ao ã
0ÞÝLW t¨Ë…£N¦- üo äL²¥ Gz [ia< Æõ1á»FbF* yØ · G¯]N<÷ýúùŒ Ü"Æ¹W# ÿŽDÓ8UÊ°XÉ0XŠíZ"ÑÅdÒÑ$æ ;i—1ªa#ÝŒ· 5HÄ¾:† ƒ Ø¯o ñîbHlz
$•dã¾'FZ J óÙ >]Ìx ö'o»¨®NÕgÇ{'ëïgò Ç=` ƒéä"±ïc>'Ú Æ©Ÿlïe¾ óf;ã1æé ÙÎ¾q-¤7ÆôpL¨ÛÏ|Ð‰ w0 +™Þ '_·AjÓ¹ (ÍÁ édÑÿ¯HÐ7z ‹óãõl#»]Õûxy÷ý?lÿ…
{ç,ï ,nÇ|9¶>~Í,‰kf²^¹ |D-'lq2yc+ ò—líÄž•Ìr;[Íÿ- ,"¼n•Wà¿®CŠª ç¹Ø›TÛ ãÑ,ñ¡3{pÆ ‹äÇ„4£1Chê¶ Õö>»s°ß*"Ø ýv±Ài³÷% E==Bƒmi·s@h° X +¬ ÉE ›¥G° Áé°tZ{-
Žå,½ë?r l}, ÇšûlNk§Ðè´8 ør_gŠÝ!ØqÄ!tØ]}N‡Í: <Æ G'Rlïéli±: (S²Ñ,ÄVÛ: ö {—3nB ›žD§W7 +ÑDo¥ ĚJ[ßR¡¶«ЁОa '„ {;jTcëè¶÷X …: Šî°Y„F«¯ y ©ÙYi v—
Ðk \ VÔ í²÷9 §]é´ ô÷à
ô;lØÙ #V|Z „~«£×æ¤f¶ 2£{Pf e ¨‡ƒõö;ì ® 'Efe7*2A >m} =®NDZ SÂP×3(ÄÚâ ko;ò?0»ï¿JgÓ;©õ ëµ'úã 'gd^¹Ì¢X JqZ{©ó 6"Úi_Ù×c·tN Á"™Ž® ÷¡Ýåìw9…Në
3Íé¶öôOFhò.WƒQ„" Fº÷L q xa„^›ÔÚÅÖãÄžrö®sbŸb›â´âUÅËx úW¥ÙþMÚ ¤º'^ kƒŽº& Îbky€åN'[["5‚†Ìåã |û öO kaoLì©`Ì Ì'É#uÈ—jçb{]£ƒÿQûl ð | ŸË—ð |_ˆgŸ*>
{Ò›M¿Še }B*öOî¥ÞèG{&É-¹¢Ðcf›Œš åT !ÿ Çz[endstream endobj 32 0 obj 6186 endobj 30 0 obj << /Type /Font /Subtype /CIDFontType2 /BaseFont /Arial-BoldMT
/CIDSystemInfo << /Registry (Adobe) /Ordering (Identity) /Supplement 0 >> /FontDescriptor 28 0 R /CIDToGIDMap /Identity /W [0 [744 276 606 606 276 552 276
552 552 552 276 936 552 606 772 330 276 662 552 386 716 552 330 606 330 552 552 276 552 552 552 330 882 606 276 552 330 552 772 662 552 552 606 716
826 552 552 552 606 606 606 716 606 330 716 716 276]] >> endobj 31 0 obj << /Length 749 >> stream /CIDInit /ProcSet findresource begin 12 dict begin
begincmap /CIDSystemInfo << /Registry (Adobe) /Ordering (UCS) /Supplement 0 >> def /CMapName /Adobe-Identity-UCS def /CMapType 2 def 1
begincodespacerange <0000> endcodespacerange 2 beginbfrange <0000> <0000> <0000> <0001> <0037> [<0049> <006E> <0064> <0069> <0061> <0009>
<0076> <0073> <002E> <0057> <0063> <006F> <004F> <0066> <006C> <0053> <0065> <0072> <0042> <0078> <0028> <0046> <0029> <0031> <0030>
<002F> <0035> <0032> <0038> <0074> <006D> <0067> <002C> <0039> <002D> <0033> <0047> <0050> <0023> <0079> <0068> <0041> <004D> <0036>
<0034> <006B> <0070> <0062> <0054> <0043> <0075> <003A> <004E> <0044> <006A>] endbfrange endcmap CMapName currentdict /CMap defineresource
pop end end endstream endobj 10 0 obj << /Type /Font /Subtype /Type0 /BaseFont /Arial-BoldMT /Encoding /Identity-H /DescendantFonts [30 0 R] /ToUnicode
31 0 R>> endobj 2 0 obj << /Type /Pages /Kids [5 0 R] /Count 1 /ProcSet [/PDF /Text /ImageB /ImageC] >> endobj xref 0 33 0000000000 65535 f 0000000009
00000 n 0000034239 00000 n 0000000241 00000 n 0000000336 00000 n 0000004190 00000 n 0000000373 00000 n 0000001471 00000 n 0000001490
00000 n 0000004120 00000 n 0000034100 00000 n 0000026177 00000 n 0000017880 00000 n 0000004140 00000 n 0000004534 00000 n 0000014164
00000 n 0000004311 00000 n 0000004514 00000 n 0000014185 00000 n 0000014449 00000 n 0000017159 00000 n 0000017409 00000 n 0000017138
00000 n 0000018021 00000 n 0000018272 00000 n 0000024858 00000 n 0000025321 00000 n 0000024837 00000 n 0000026311 00000 n 0000026567
00000 n 0000032864 00000 n 0000033300 00000 n 0000032843 00000 n trailer << /Size 33 /Info 1 0 R /Root 13 0 R >> startxref 34337 %%EOF